

# Tiger Features



## BRUSH CUTTER HEAD

Cuts brush up to 4" with 360° rotating knives. Adjustable rear roller.



## GRASS CUTTER HEAD

Drop forged steel unbreakable cutter knives. Safety rubber flap, front or rear mount. Adjustable rear roller. Unique sliding mount system for added cutter arc.



## CABLE CONTROLS

Independent cable control standard

# Tiger Specifications

	RBF-2C	RBF-12C	RBF-14C	RBF-19C
Reach Out	10' 7"	12' 9"	14' 9"	19' 2"
Reach Up	-	11' 3"	15' 10"	20' 8"
Reach Down @ 45°	-	7' 9"	9' 7"	14' 9"
Cutting Head Width	63"	37"	43"	50"
Break Away	Mechanical	Mechanical	Hydraulic	Mechanical/Hydraulic
<b>Requirements</b>				
Minimum Tractor	55 HP	40 HP	55 HP	65 HP
Hitch	PTO 1,000/540 Cat. II	PTO 540 Cat. II	PTO 540 Cat. II	PTO 540 Cat. II
Hyd Outlets	2	-	-	-
Shipping Weight	1256 lbs.	1111 lbs.	1672 lbs.	2068 lbs.

Reach measured from tractor center line and may vary depending upon tractor and/or tire configuration.

## Dealer Info:

Tiger Corporation  
3301 N. Louise Ave.  
Sioux Falls, SD 57107  
800.843.6849  
www.tiger-mowers.com  
An Alamo Group® Company

Specifications are subject to change without notice.  
Optional equipment may be shown.  
One Year Warranty on all products.

© 2006 Tiger Corporation. All Rights Reserved. Printed in the USA.

# Tiger™ FLAIL ROADSIDE MOWERS

## Rear Flail Mowers



RBF-19C



RBF-2C

DURABILITY INNOVATION  
COMMITMENT

# Rear Flail Mowers



**Compare the advantages of the quick-detachable Tiger Rear Flail Mowers. You'll discover why Tiger mowers have satisfied thousands of owners year after year. The quality and it's value are second to none. Unrestricted visibility, and ease of operation make mowing jobs fast, economical and efficient.**

**RBF-19C**



**RBF-2C**

Hydraulic side shift 2'6" with cutter reaching 10'7". Capable of a 90° reach above to 50° below horizontal. Auto returning breakout protection.



**RBF-12C**

Mounts and dismounts in minutes. Cutter reach of 12'9" and fits tractors as small as 40 PTO HP. Auto returning mechanical breakout.



**RBF-14C**

Simple, self contained 3 pt. hitch mounting and side reach of 14'9". Operator friendly remote cable controlled valving. Hi-torque drive system for tough conditions.



**RBF-19C TRANSPORT**

Double action forward and rearward breakout with a reach of 19'2". Sliding head mounting system mounts to 3 pt. hitch driven by 540 PTO.